

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Paint Ceramic Coat

UFI: D910-S04G-100P-R0FW

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Special finishes, Plating agent, Waterproofing agent

1.3. Details of the supplier of the safety data sheet

Company name:	ZviZZer International GmbH	
Street:	Grube Weiß 26	
Place:	D-51429 Bergisch Gladbach	
Telephone:	+49 177 3016109	
E-mail:	info@zvizzer.com	
Contact person:	Detlef Finken	Telephone: +49 177 3016109
E-mail:	info@zvizzer.com	
Internet:	www.zvizzer.com	
Responsible Department:	Giftinformationszentrale Mainz	

1.4. Emergency telephone number:German & English 24h: +49 6131 19240
Russian 24h: +74953634008**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Flam. Liq. 2; H225
Acute Tox. 4; H302
Asp. Tox. 1; H304
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
3-aminopropyltriethoxysilane**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 2 of 12

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

Vapours can form explosive mixtures with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with			50 - < 55 %
	Flam. Liq. 2, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H225 H302 H314 H318 H412			
	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	926-141-6		01-2119456620-43	
	Asp. Tox. 1; H304 EUH066			
919-30-2	3-aminopropyltriethoxysilane			1 - < 5 %
	213-048-4	612-108-00-0		
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1; H302 H314 H318 H317			
142-96-1	di-n-butyl ether; dibutyl ether			1 - < 5 %
	205-575-3	603-054-00-9	01-2119982240-42	
	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 3; H226 H315 H319 H335 H412			
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			1 - < 5 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
475645-84-2		Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with	50 - < 55 %
		oral: LD50 = > 300 - 2000 mg/kg	
	926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
919-30-2	213-048-4	3-aminopropyltriethoxysilane	1 - < 5 %
		oral: ATE = 500 mg/kg	
142-96-1	205-575-3	di-n-butyl ether; dibutyl ether	1 - < 5 %
		inhalation: LC50 = 21,6 mg/l (vapours); dermal: LD50 = 7741 mg/kg; oral: LD50 = 7400 mg/kg STOT SE 3; H335: >= 10 - 100	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 4 of 12

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove persons to safety. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

storage temperature: 10 - 25 °C

Protect against: frost. UV-radiation/sunlight.

Maximum storage period (time) 12 month(s)

7.3. Specific end use(s)

Special finishes, Plating agent, Waterproofing agent

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 5 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			
Worker DNEL, long-term		inhalation	systemic	67,5 mg/m³
Worker DNEL, long-term		inhalation	local	67,5 mg/m³
Worker DNEL, acute		inhalation	local	101,2 mg/m³
Worker DNEL, long-term		dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	34 mg/m³
Consumer DNEL, acute		inhalation	local	34 mg/m³
Consumer DNEL, long-term		inhalation	local	50,6 mg/m³
Consumer DNEL, long-term		dermal	systemic	10 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,25 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment		Value
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	
Freshwater		1 mg/l
Freshwater (intermittent releases)		3,9 mg/l
Marine water		0,1 mg/l
Freshwater sediment		4 mg/kg
Marine sediment		0,4 mg/kg
Secondary poisoning		56 mg/kg
Micro-organisms in sewage treatment plants (STP)		200 mg/l
Soil		0,4 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 6 of 12

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless, clear
Odour:	characteristic
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	(Cyclosilazanes, di-Me, Me hydrogen, po
Flammability:	not applicable
	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	(Cyclosilazanes, di-Me, Me hydrogen, po
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	Immiscible
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,875 g/cm ³
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive.

Vapours can form explosive mixtures with air.

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Viscosity / dynamic:

not determined

Further Information

Odour threshold: not determined

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 7 of 12

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Harmful if swallowed.

ATEmix calculated

ATE (oral) 925,9 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with				
	oral	LD50 > 300 - 2000 mg/kg	Rat	Manufacturer	OECD 423
	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Manufacturer	OECD 402
919-30-2	3-aminopropyltriethoxysilane				
	oral	ATE 500 mg/kg			
142-96-1	di-n-butyl ether; dibutyl ether				
	oral	LD50 7400 mg/kg	Rat	Manufacturer	OECD 401
	dermal	LD50 7741 mg/kg	Rabbit	Manufacturer	OECD 402
	inhalation (4 h) vapour	LC50 21,6 mg/l	Rat	Manufacturer	OECD 403

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminopropyltriethoxysilane)

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 8 of 12

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with					
	Acute fish toxicity	LC50 mg/l	57,1	96 h	Danio rerio (zebrafish)	Manufacturer OECD 203
142-96-1	di-n-butyl ether; dibutyl ether					
	Acute fish toxicity	LC50 mg/l	32,3	96 h	Pimephales promelas (fathead minnow)	Manufacturer OECD 203
	Acute algae toxicity	ErC50 mg/l	11,5	72 h	Pseudokirchneriella subcapitata	Manufacturer OECD 201
	Acute crustacea toxicity	EC50	26 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	0,5 h	Activated sludge	Manufacturer OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	Water	69 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			
142-96-1	di-n-butyl ether; dibutyl ether			
	OECD 301D	5 %	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-96-1	di-n-butyl ether; dibutyl ether	3,21

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 9 of 12

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 2924

14.2. UN proper shipping name:

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3+8



Classification code:

FC

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

338

Tunnel restriction code:

D/E

Inland waterways transport (ADN)**14.1. UN number or ID number:**

UN 2924

14.2. UN proper shipping name:

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3+8



Classification code:

FC

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 10 of 12

Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8



Special Provisions: A3
Limited quantity Passenger: 0.5 L
Passenger LQ: Y340
Excepted quantity: E2
IATA-packing instructions - Passenger: 352
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 363
IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 75

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 11 of 12

Directive 2004/42/EC on VOC in
paints and varnishes:

Information according to Directive
2012/18/EU (SEVESO III):

< 85 %

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Corr: Skin corrosion

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

**Safety Data Sheet**

according to UK REACH Regulation

Paint Ceramic Coat

Revision date: 28.02.2024

Product code: ZV-CC00050B

Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H302	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)